



Specifications

1.Photos








AUPU
MACHINERY
Professional Waste Dispose System
AUPU MACHINERY
Audited Supplier
SGS
ISO 9001
CQC
TÜVRheinland
Precisely Right.

2. Y81F-200B Technical parameter

Type		Y81F-250B	Y81F-200B
The packet method		turn	
The nominal thrust	The pressure cylinder	2500KN	2000KN
	Lateral pressure cylinder	1200KN*2	1000KN*2
	Door cover oil cylinder	1000KN	800KN
	The packet cylinder	800KN	630KN
Stroke	The pressure cylinder	1000mm	800mm
	Lateral pressure cylinder	1500mm	1200mm
	Door cover oil cylinder	1270mm	1160mm
	The packet cylinder	360mm	360mm
Compression chamber size		2000*1400*900mm	1800*1200*900mm
Packet block size		500*500*400-1000	500*500*400-1000
The production efficiency		5000-6000(KG/H)	3000-5000(KG/H)
The system pressure		25Mpa	
Pump		160YCY14-1B*2	80YCY14-1B*2
A single cycle time		≤130s	≤160s
Power		22KW*2	18.5KW*2
The motor speed （r/min）		980	
Pump discharge （ml/r）		160	80
Tank capacity （L）		2500	2300
Weight of machine		21 tons	13 tons
Delivery time		30 days	30 days
Quotation have deadline		30 days	

3. Configuration：

A. Electrical：French Schneider

B. Oil Pump：Qidong High pressure oil pump

C. Oil cylinder seals：Germany USK


D. Oil pipe seals: Germany FOLON.A



E. Pressure gauge: USA Joseph KK

F. High pressure hose: Pikes

G. The tubing connector: USA EATON

HONORARY CERTIFICATE






HONORARY CERTIFICATE



