



Specifications

1.Photos







2. Y81F-160A Technical parameter

TYPE		Y81-160A	
The packet method		turn	
The nominal thrust	The pressure cylinder	1600KN	
	Lateral pressure cylinder	1250KN	
	Door cover oil cylinder	630KN	
	The packet cylinder	630KN	
Stroke	The pressure cylinder	750MM	
	Lateral pressure cylinder	1200MM	
	Door cover oil cylinder	1150MM	
	The packet cylinder	365MM	
Compression chamber size （L×W×H）		1600*1000*800MM	
Packet block size （L×W×H）		400*400*(300-1000)	
Block density		≥1800 kg/m ^ 3	
The production efficiency		2000-3500KG/H	
The system pressure		25Mpa	
Pump		160YCY14-1B	
Pump discharge		160ml/r	
A single cycle time		≤110s	
Voltage		380V，50Hz	
Power		22KW	
The motor speed （r/min）		970	
Pump discharge （ml/r）		63*2	160
Tank capacity （L）		1400	1200
Size of machine(mm)		4300x3000x2600	
Weight of machine		10.5tons	
Manner of packing		nude packing	
Delivery time		30 days	
Quotation have deadline		30 days	

3. Configuration：

A. Electrical：French Schneider

B. Oil Pump：Qidong High pressure oil pump

C. Oil cylinder seals：Germany USK


D. Oil pipe seals: Germany FOLON.A



E. Pressure gauge: USA Joseph KK

F. High pressure hose: Pikes

G. The tubing connector: USA EATON

HONORARY CERTIFICATE






HONORARY CERTIFICATE



